UPG No. 40596

UPG Sealed Lead-Acid Battery

UB26-12T

Maintenance-Free

Absorbant Glass Mat (AGM) technology for superior performance. Valve regulated, spill proof construction allows safe operation in any position. Approved for transport by air. D.O.T., I.A.T.A., F.A.A. and C.A.B. certified. U.L. recognized under file number MH 20567.

Specification

Nominal Voltage	12 volts
Nominal Capacity	77º F (25º C)
20-hr. (1.30A)	26.0 Ah
10-hr. (2.40 A)	24.0 Ah
5-hr. (4.40 A)	22.0 Ah
1-hr. (15.5 A)	15.5Ah
Approximate Weight	17.9 lbs (8.1 kgs)
Internal Resistance (approx.)	10mΩ

Shelf Life (% of normal capacity at 68º F (20º C)

3 Months	6 Months	12 Months
91%	83%	64%

Temperature Dependancy of Capacity (20 hour rate)

104˚ F (40˚C)	77˚F (25˚C)	32˚F (0˚C)	5˚F (-15˚C)
102%	100%	85%	65%


AGM Operational Temperature	
Charge	32˚F to 104˚F (0˚C to 40˚C)
Discharge	5˚F to 113˚F (-15˚C to 45˚C)
AGM Storage Temperature	5˚F to 104˚F (-15˚C to 40˚C)



Due to continuous improvements to our products, product may vary slightly from depiction.


Charge Method (Constant Voltage)	
Cycle Use (Repeating Use)	
Initial Current	7.8A or smaller
Control Voltage	14.6 - 14.8 V
Float Use	
Control Voltage	13.6 - 13.8 V

Physical Dimensions: in (mm)



L: 6.50 in (165 mm)
W: 4.96 in (126 mm)
H: 6.89 in (175 mm)
TH: 7.05 in (179 mm)
Tolerances are +/- 0.04 in. (+/- 1mm) and +/- 0.08 in. (+/- 2mm) for height dimensions. All data subject to change without notice.


Terminals




L Series (L Type Terminal)

Dimension / Type	L	W	H	h	⌀
L2	17.0	9.0	17.0	9.0	6.5

Discharge Time vs. Discharge Current



Discharge Characteristics




488 S. Royal Lane | Coppell, Texas 75019 | P 469.892.1122 | T 866.892.1122 | F 469.892.1123 | sales@upgi.com

Copyright©2017 Universal Power Group. All rights reserved.


UB26-12T

Maintenance-Free


Shelf Life & Storage




Cycle Life vs Depth of Discharge



Open Circuit Voltage vs Residual Capacity



Effect of Temperature on Capacity



Charge Current & Final Discharge Voltage

Application	Charge Voltage(V/Cell)			Max.Charge Current
	Temperature	Set Point	Allowable Range	
Cycle Use	25℃(77℉)	2.45	2.43~2.47	0.30C
Standby	25℃(77℉)	2.28	2.27~2.30	

Final Discharge Voltage V/Cell	1.75	1.70	1.60	1.30
Discharge Current(A)	0.2C>(A)	0.2C<(A)<0.5C	0.5C<(A)<1.0C	(A)>1.0C