

Specification

Nominal Voltage	12 volts		
Nominal Capacity	77° F (25° C)		
20-hr. (0.04 A)	0.80 Ah		
10-hr. (0.07 A)	0.74 Ah		
5-hr. (0.14 A)	0.68 Ah		
1-hr. (0.52 A)	0.52 Ah		
Approximate Weight	0.75 lbs (0.3 kgs)		
Internal Resistance (approx.)	200mΩ		
Shelf Life (% of normal capacity at 68°F (20° C)			
3 Months	6 Months	12 Months	
91%	83%	64%	
Temperature Dependency of Capacity	(20 hour rate)		
104° F	77° F	32° F	5° F
102%	100%	85%	65%
AGM Operational Temperature			
Charge	32°F to 104°F (0°C to 40°C)		
Discharge	5°F to 113°F (-15°C to 45°C)		
AGM Storage Temperature	5°F to 104°F (-15°C to 40°C)		



Charge Method (Constant Voltage)


Cycle Use (Repeating Use)

Initial Current	0.24A or smaller
Control Voltage	14.6 - 14.8

Float Use


Control Voltage	13.6 - 13.8
-----------------	-------------

Physical Dimensions: in (mm)




L: 3.78in (96.0 mm)
W: 0.98in (24.9 mm)
H: 2.44in (62.0 mm)
TH: 2.44in (62.0 mm)
 Tolerances are +/- 0.04 in. (+/- 1mm) and +/- 0.08 in. (+/- 2mm) for height dimensions. All data subject to change without notice.


Terminals




Discharge Time vs. Discharge Current




Discharge Characteristics




Shelf Life & Storage




Cycle Life vs Depth of Discharge



Open Circuit Voltage vs Residual Capacity



Effect of Temperature on Capacity



Charge Current & Final Discharge Voltage

Application	Charge Voltage(V/Cell)			Max.Charge Current	Final Discharge Voltage V/Cell	1.75	1.70	1.60	1.30
	Temperature	Set Point	Allowable Range						
Cycle Use	25°C(77°F)	2.45	2.40~2.47	0.30C	Discharge Current(A)	0.2C>(A)	0.2C<(A)<0.5C	0.5C<(A)<1.0C	(A)>1.0C
Standby	25°C(77°F)	2.28	2.27~2.30						